AS016-35SN ACTIVE

DEUTSCH | DEUTSCH AS Standard

TE Internal #: AS016-35SN

Standard Circular Connectors, Wire-to-Wire, 55 Position, Sealable, Black Zinc, Aluminum Alloy, N Polarization Code, DEUTSCH AS

Standard

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors



Connector System: Wire-to-Wire

Number of Positions: 55

Sealable: Yes

Shell Plating Material: Black Zinc
Shell Base Material: Aluminum Alloy

Features

Product Type Features

Product Type	Connector
Assembly Type	Electrical Connector
Connector System	Wire-to-Wire
Sealable	Yes
Circular Connector Type	Receptacle

Configuration Features

Factory Installed Backshell	No
Keying	Keyway Polarization N
Number of Positions	55
Contacts Preloaded	No

Body Features

Environmental Protection	With
Feedthrough Type	No
Environmental Protection Type	Sealed
Entry Style	Rear Insertion
Shell Plating Material	Black Zinc



Shell Base Material	Aluminum Alloy
Circular Connector Insulation Material Type	Hard Dielectric/Silicone
Hermetically Sealed	No
Contact Features	
Contact Quantity (Size 22D)	55
Contact Layout Arrangement	16 – 35
Circular Connector Contact Type	Socket
Mechanical Attachment	
Mating Retention Type	Bayonet Peg
Mating Alignment	With
Panel Mount Feature Type	2 Hole Flange
Polarization Code	N
Mating Alignment Type	Keyed
Mating Retention	With
Housing Features	
Circular Connector Shell Size	16
Dimensions	
Assembly Length	33.5 mm
Wire Size	22 AWG
Usage Conditions	
Fluid Resistance	Immersible
IP Dust Sealing Level	6
IP Water Sealing Level	7
Operating Temperature Range	-55 – 175 °C
Operation/Application	
Durability Rating	500 Cycles
Other	
Field Serviceable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU Compliant with Exemptions	
--	--



EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUN 2020 (209) SVHC > Threshold: Pb (1.2% in Contact) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | DEUTSCH AS Standard





Documents

Product Drawings
RECEPT.2 HOLE MNT.TYPE 0

English

Datasheets & Catalog Pages
AS Micro Xtra Lite HE

English